


Accessories for welded and Connex systems and ropes

WLHW swivel safety hook (self locking)



Standard type must not be swivelled when loaded.
Not for welded system!

WLHBW swivel safety hook (self locking)

Swivel hook with bearing to rotate when loaded.
Not for welded system!

Code Code Código	Load capacity Charge max. d'utilisation Capacidad d de carga kg	e mm	h mm	a mm	w mm	w1 mm	d2 mm	g mm	s max. mm	Weight kg/pc. Poids kg/pièce Peso kg/Unid.
WLHW 6	1.400	160	20	17	35	35	13	28	1	0,60
WLHW 7/8	2.500	181	26	20	35	35	13	34	1	1,10
WLHW 10	4.000	218	30	29	42	40	16	45	1	2,00
WLHW 13	6.700	269	40	35	49	47	20	52	2	4,00
WLHW 16	10.000	319	50	41	60	60	24	60	2	6,80

Code Code Código	Load capacity Charge max. d'utilisation Capacidad d de carga kg	e mm	h mm	a mm	w mm	w1 mm	d2 mm	g mm	s max. mm	Weight kg/pc. Poids kg/pièce Peso kg/Unid.
WLHBW 6	1.400	160	20	17	35	35	13	28	1	0,60
WLHBW 7/8	2.500	181	26	20	35	35	13	34	1	1,10
WLHBW 10	4.000	218	30	29	42	40	16	45	1	2,00
WLHBW 13	6.700	269	40	35	49	47	20	52	2	4,00
WLHBW 16	10.000	319	50	41	60	60	24	60	2	6,80